

Technical Data Sheet

MAESTRO PARQUET RETARDER

Agent for delaying the cross-linking of Maestro 2K
PU laquer



product description: MAESTRO retarder is a mixture of organic solvents.

intended use: It is used if it is necessary to slow down the initial drying for better spreading.

A maximum of 10% is added when mixing the final layer of matte/semi-matt laquer and contact, and a maximum of 5% when mixing the final layer of glossy lacquer and contact.

assortment: MAESTRO retarder

appearance: Clear, colourless to yellowish liquid

density: 0.97 kg/l (EN ISO 2811-1)

transport and storage: Store in a dry and well-ventilated place out of direct sunlight at a temperature of +5 to +25 °C.

shelf life: In unopened packaging unlimited from the date of manufacture.

certificates: For each production batch, the relevant documentation is submitted.

product/packaging disposal: Empty the packaging completely. Dispose of in accordance with valid regulations to an authorized waste collector.

quality control: Product quality characteristics are determined by internal production specifications and European and Croatian standards. The product is under the constant supervision of factory quality control Chromos-Svjetlost d.o.o.

disclaimers: Before using the product, please check its quality. In case of any major deviations from the declared properties of the product, stop the use and contact the manufacturer; otherwise any subsequent complaints will not be accepted.

Technical data are the result of our technical and experimental knowledge, and are provided with the intention of achieving optimal results in working with CHROMOS- SVJETLOST products. The data does not contain a legal or secondary obligation of the manufacturer nor does it release the user from the obligation to check the suitability of the product for particular purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible for individual deliveries. Contact our Technical service before use on substrates not listed in the accompanying documentation. The manufacturer reserves the right to make any subsequent changes to the Technical Data Sheet. Only the latest edition is valid. Updated Technical Data Sheets can be found on the website www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail address below. Contact our Technical service for more detailed information. Be sure to read the safety labels on the product packaging before use. Safety Data Sheet is available on request.

October, 2021.

Quality and Environmental management systems certified in accordance with TÜV NORD Croatia;
Certificate No: 44 100 134668 / 44 104 134668

